

Nastri trasportatori in con tappeto modulare in plastica - Struttura in acciaio verniciato
Modular plastic conveyor belts - Painted steel frame

Serie | Series
2000

P2450

Orizzontale/Inclinato
Horizontal/Incline



IT SPECIFICHE TECNICHE:	EN TECHNICAL SPECIFICATIONS:		
Dimensioni	a seconda dell'applicazione	Dimensions	depends on the application
Struttura	acciaio verniciato	Frame	2 mm thick painted steel
Sponde	integrate nella struttura in acciaio verniciato sponde aggiuntive in acciaio inossidabile	Sidewalls	painted steel integrated with the frame additional stainless steel sidewalls
Supporti di sostegno	cannocchiali in acciaio verniciato gambe in tubolari in metallo zincato ruote pivotanti con freno	Stand supports	painted steel clamps zinc plated steel legs castors with brakes
Tappeto	ampio range di tappeti in PP	Belt	wide range of solutions in PP
Trasmissione	diretta in traino (lato sinistro) motoriduttore asincrono - 3F - 4poli - 400Vac - 50Hz	Drive	direct (left side) 3 Phase - 400Vac/50Hz asynchronous motor
Velocità	6 m/min	Speed	6 m/min
Controllo	Start - Stop	Control	Start - Stop



PL MACHINERY SERVICES & SALES LTD
UNIT A3/A4 BARTON INDUSTRIAL ESTATE, FALDO ROAD,
BARTON LE CLAY, BEDFORDSHIRE, MK45 4RP
TEL: 01582 883666 / EMAIL: sales@plmachinery.com