

## **4000 SERIES**



Drum separator with quick roller adjustment

	<b>Ø 450 x 650</b>	<b>Ø 450 x 950</b>
Rulli in PVC   PVC rollers	S4100	S4110
Rulli in AISI304   AISI304 rollers	S4120	S4130

### **S41xx – Technical Specifications**

<b>Description</b>	Rotating drum separator with rollers
<b>Frame</b>	6060 anodized extruded aluminium profile 35x35mm (3 sides) and 80x30 (1 side) AISI430 lateral/frontal protection, in/out ring and vertical/incline adjustable in feed chute 3mm PC removable upper protection
<b>Leg</b>	Telescopic perforated zinc plated telescopic steel legs 30x70mm, vertical/incline adjustment (0°-30°)
<b>End leg</b>	Metal black painted "C" base
<b>Rotating drum</b>	Ø 450mm, 10 adjustable gaps 0÷50mm, fast adjustment by single screw®
<b>Rollers</b>	20 PVC rollers Ø50x627mm
<b>Drive</b>	Direct
<b>Asynchronous Motor</b>	3PH 4poli (1360rpm) – 400Vac/50Hz
<b>Power</b>	0,04KW
<b>Gear box with permanent lubrication</b>	i=1/15
<b>Speed</b>	Adjustable speed with 3 steps pulley
<b>Control Panel</b>	IP55, thermal overload protected motor starter (on/off), emergency button, five cores (5x1,5mm) cable length 3000mm flame-retardant



**PL MACHINERY SERVICES & SALES LTD**  
 UNIT A3/A4 BARTON INDUSTRIAL ESTATE, FALDO ROAD,  
 BARTON LE CLAY, BEDFORDSHIRE, MK45 4RP  
 TEL: 01582 883666 / EMAIL: [sales@plmachinery.com](mailto:sales@plmachinery.com)