

## 4000 SERIES



### S4600 to S4610 – Technical Specification

<b>Description</b>	2 rollers separator
<b>Frame</b>	6060 anodized extruded aluminium profile 40x40mm AISI430 lateral/frontal protection and inlet/outlet chute 3mm PC removable upper protection
<b>Leg</b>	Perforated zinc plated steel legs 35x35x1000mm, vertical/incline adjustment (0°-20°)
<b>End leg</b>	Metal black painted base with 2 wheels Ø 60mm and 2 legs
<b>Rotating rollers</b>	PVC, Ø140x600mm, adjustable gaps 0-40mm by worm screw
<b>Drive</b>	Direct
<b>Asynchronous Motor</b>	3PH 4poli (1360rpm) – 400Vac/50Hz
<b>Power</b>	0,04KW
<b>Gear box with permanent lubrication</b>	i=1/15
<b>Speed</b>	Fixed
<b>Control Panel</b>	IP55, thermal overload protected motor starter (on/off), emergency button, five cores (5x1,5mm) cable length 3000mm flame-retardant



PL MACHINERY SERVICES & SALES LTD  
 UNIT A3/A4 BARTON INDUSTRIAL ESTATE, FALDO ROAD,  
 BARTON LE CLAY, BEDFORDSHIRE, MK45 4RP  
 TEL: 01582 883666 / EMAIL: [sales@plmachinery.com](mailto:sales@plmachinery.com)