

4000 SERIES



Reduced diameter drum separator

	Ø 310 x 650	Ø 310 x 950
Rulli in PVC PVC rollers	S4300	S4310

S43xx – Technical Specification

Description	Rotating drum separator with rollers
Frame	6060 anodized extruded aluminium profile 35x35mm (3 sides) and 80x30 (1 side) AISI430 lateral/frontal protection, in/out ring and vertical/incline adjustable in feed chute 3mm PC removable upper protection
Leg	Perforated zinc plated steel legs 35x35x1000mm, vertical/incline adjustment (0°-20°)
End leg	Metal black painted base with 2 wheels Ø 60mm and 2 legs
Rotating drum	Ø340mm, 15 adjustable gaps 0-50mm, progressive adjustment by screws
Rollers	20 PVC rollers Ø40x627mm
Drive	Direct
Asynchronous Motor	3PH 4poli (1360rpm) – 400Vac/50Hz
Power	0,04KW
Gear box with permanent lubrication	i=1/15
Speed	Adjustable speed with 3 steps pulley
Control Panel	IP55, thermal overload protected motor starter (on/off), emergency button, five cores (5x1,5mm) cable length 3000mm flame-retardant



PL MACHINERY SERVICES & SALES LTD
UNIT A3/A4 BARTON INDUSTRIAL ESTATE, FALDO ROAD,
BARTON LE CLAY, BEDFORDSHIRE, MK45 4RP

TEL: 01582 883666 / EMAIL: sales@plmachinery.com