

MAINTech PLASTICS ENGINEERING

TECHNICAL DATA SHEET

ASC / ASM SERIES SINGLE PHASE HOPPER LOADERS

		ASC-1 +TRMX1	ASC-1	ASM-2	ASM-10	ASM-15
Voltage	V/-Hz	230/1/50-60 Hz	230/1/50-60 Hz	230/1/50-60 Hz	230/1/50-60 Hz	230/1/50-60 Hz
Throughput	Kg/h	25- 50	25/50	50	90	160
Motor Power	kW	/	/	1	1	1
Static Depression	kPa(mbar)	/	/	21 (210)	21 (210)	21 (210)
Capacity	dm ³	0,9	/	2	10	15
Compressed Air Pressure	kPa (bar)	600-800 (6-8)	600-800 (6-8)	600-800 (6-8)	600-800 (6-8)	600-800 (6-8)
Compressed Air Consumption Cycle	NI	550NI/m	550NI/m	3	6	6
Dimensions	mm A	310	162	511	615	690
Dimensions	mm B	/	/	540	738	813
Weight	Kg	6	2	7	13	14
Noise Level	dB (A)	<76	<76	<76	<76	<76
Maximum Process Temperature	°C	80	80	80	80	80
Diameter of the loading pipe	Ømm	30	30	40	40	40