


BOE-THERM

Your reliable
partner in
Temperature
Control Units



TEMP 95S

Pressurized-water temperature control unit up to 95 °C

- ❖ Energy efficient pump
- ❖ Easy operation
- ❖ Temperature deviation alarm function
- ❖ Low noise




P machinery

BOE-THERM

TEMP 95S

Equipment:	Standard	Optional
Automatic restart	•	
Temperature deviation alarm	•	
Automatic water refilling	•	
Leakage control during operation	•	
Pressure relief after stop		•
Mould draining		•
Automatic cool down function	•	
Flow measuring Vortex		•
Connection for external PT 100 sensor		•
Service indicator (hour counter)	•	
Serial interface 20 mA CL		•
Analog interface 4-20 mA		•
Profibus		•
Ethernet/IP		•
Profinet		•
Devicenet		•



Technical Specifications:

Max outlet temperature	95 °C			
Heating capacity	4,5 kW (opt. 9 - 13,5 - 18kW)			
Heat transfer fluid	Water			
Tank volumen	6 Liter			
Pump	std.			
Type	M3	M4	M5	
Flow rate max. l/min	75	85	115	
Pressure max. Bar	2,8	5,6	5,8	
Power kW	0,5	1	1,5	
Cooling capacity at $\Delta T = 60$ °C	std.			
Type	I2	I4	D2	D4
kW	15	28	42	175
Connections in/out	1/2"			
Operating voltage std.	3x400V/50Hz			
Dimensions (W x H x D)	270 x 650 x 680 mm			